

PRODUCT INFORMATION

NO MORE STAINS

Page 1 of 1

Manufacturer's Code: RPNMS

Updated: 22/09/2014

Product Name: NO MORE STAINS

Description: NO MORE STAINS is an innovative cleaner specially formulated to remove organic stains from masonry surfaces.

Recommended Uses: NO MORE STAINS is suitable to remove organic stains particularly timber stains from masonry surfaces such as concrete blocks, pavers, sandstone products and other masonry substrates.

Use Instructions: Brush NO MORE STAINS over the staining area and leave it for 5-10 minutes or until stains disappear. Flush the surface with clean water. Repeat this as often as required until all stains are removed.

Typical Data:

Appearance:	Colourless liquid with strong odour
Solids content:	<50% by weight
Specific Gravity:	1.2 g/ml at 20 °C
pH value:	>10
Solubility in water:	Soluble in water
VOC content:	Nil
Flash point:	Not allocated

Important Note: As masonry materials vary significantly, it is strongly recommended that a pilot test must be carried out prior to application to find out the suitability of this product for the purposes.

Handling & Storage: NO MORE STAINS has strong alkalinity and is corrosive. Vapour inhalation and skin or eye contact should be avoided by wearing proper protection. Wear an air-purifying respirator if there is a risk of exposure to high vapour concentrations. Wash hands after handling. **Keep product away from Aluminium.** The product should be stored in closed containers in a cool dry place away from any fire and ignition sources. The product has a shelf life of 3 months in a sealed original container under 25°C. However, if the product is passed its use-by-date, it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice.

Use with sufficient ventilation!

Keep out of reach of children!

Packaging: NO MORE STAINS is available in 20 and 200 litre plastic drums.

Disclaimer:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material are beyond our control; we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application.